



606

PISTON SEAL

*Single-Acting
Polyurethane, Single Lip*

DESIGN

The Hallite 606 single-acting, single lip asymmetric piston seal is designed with precision trimmed sealing lips to provide effective bore sealing in light and medium-duty applications. The seal can be considered for use in heavy-duty applications when used with a suitable full depth back-up ring. The sealing lips are trimmed at an angle to give optimal rod sealing performance.

The range covers most standard housings used in Europe, North America and Asia.

The Hallite 606 is designed to have an interference in the seal housing groove.

The outer dynamic lip is shorter and more robust to improve sealing and compression set characteristics over conventional, symmetrical U-rings.

The seal is recommended for use in single-acting piston seal applications.

It can also be fitted back-to-back in separate grooves for use in double-acting applications.

The Hallite 606 is molded in Hythane® 181, Hallite's high-performance polyurethane, for easy installation and excellent low temperature performance.



FEATURES

- General purpose seal
- Robust design
- Excellent wear resistance
- Performs well over wide temperature range and is extremely effective in low temperatures
- Easy to install

MATERIALS

As standard, this product comes in the following material. Contact your local Hallite technical team if you would like to find out if this profile can be made in a custom material to suit your application. For further material details, please refer to the Hallite Material Table.

| MATERIAL OPTIONS | Name | Type | Color |
|------------------|--------------|--------|-------|
| Standard | Hythane® 181 | TPU-EU | Blue |



TECHNICAL DETAILS

| OPERATING CONDITIONS | METRIC | INCH |
|-----------------------------------|--------------|--------------|
| Maximum Speed | 1.0 m/sec | 3.0 ft/sec |
| Temperature Range | -45°C +110°C | -50°F +230°F |
| Maximum Pressure | 400 bar | 6000 psi |
| Maximum Pressure with Backup Ring | 700 bar | 10000 psi |

NOTE

Data given are maximum values and can apply depending on specific application. Maximum ratings of temperature, pressure, or operating speeds are dependent on fluid medium, surface, gap value, and other variables such as dynamic or static service. Maximum values are not intended for use together at the same time, e.g. max temperature and max pressure. Please contact your Hallite technical representative for application support.

NOTE

Pressure Rating: Can be extended with use of back-up ring. Seek technical advice from local Hallite office.

| MAXIMUM EXTRUSION GAP | | | |
|-----------------------|-------|-------|-------|
| Pressure bar | 160 | 250 | 400 |
| Maximum Gap mm | 0.60 | 0.50 | 0.40 |
| Pressure psi | 2400 | 3750 | 6000 |
| Maximum Gap in | 0.024 | 0.020 | 0.016 |

NOTE

Figures show the maximum permissible gap all on one side, for rod seals using minimum rod \varnothing and maximum clearance \varnothing and for piston seals using the minimum clearance \varnothing and maximum bore \varnothing . Refer to Housing Design section.

| SURFACE ROUGHNESS | μmRa | μmRz | μmRt | μinRa | μinRz | μinRt |
|----------------------------------------|-----------------|-----------------|-----------------|------------------|------------------|------------------|
| Dynamic Sealing Face $\varnothing D_1$ | 0.1 - 0.4 | 1.6 max | 4 max | 4 - 16 | 63 max | 157 max |
| Static Sealing Face $\varnothing d_1$ | 1.6 max | 6.3 max | 10 max | 63 max | 250 max | 394 max |
| Static Housing Faces L_1 | 3.2 max | 10 max | 16 max | 125 max | 394 max | 630 max |

| CHAMFERS & RADII | | | | | | |
|----------------------------|-------|-------|-------|-------|-------|-------|
| Groove Section $< S$ mm | 4.00 | 5.00 | 7.50 | 10.00 | 12.50 | 15.00 |
| Min Chamfer C mm | 3.00 | 3.50 | 5.00 | 6.50 | 7.00 | 8.00 |
| Max Fillet Rad r_1 mm | 0.20 | 0.40 | 0.80 | 0.80 | 1.20 | 1.60 |
| Max Fillet Rad r_2 mm | 0.40 | 0.80 | 1.20 | 1.20 | 1.60 | 2.40 |
| Groove Section $\leq S$ in | 0.125 | 0.187 | 0.250 | 0.312 | 0.375 | 0.500 |
| Min Chamfer C in | 0.093 | 0.093 | 0.125 | 0.156 | 0.187 | 0.187 |
| Max Fillet Rad r_1 in | 0.008 | 0.008 | 0.016 | 0.032 | 0.032 | 0.032 |
| Max Fillet Rad r_2 in | 0.016 | 0.016 | 0.032 | 0.047 | 0.047 | 0.047 |

| TOLERANCES | $\varnothing D_1$ | $\varnothing d_1$ | L_1 |
|------------|-------------------|-------------------|-----------|
| mm | H9 | js11 | +0.25 -0 |
| in | H9 | js11 | +0.010 -0 |

